


Type .1



Type.2

NO.		Type	尺寸(Unit: mm)							磁心参数				Al-value (nH/N ²)±25%					功耗Max (W/set)					重量 (g/set)		
			A	B	C	D	E	F	F1	C1	Le	Ae	Ve	Al-value					功耗Max							
			(mm ⁻¹)	(mm)	(mm ²)	(mm ³)	KP4	KP44	KP44A	KP47	KP90	KP95	KP4	KP44	KP44A	KP47	KP90	KP95								
EE48-1	EE4817	1	48.0±0.5	9.05±0.15	21.0+0.2/-0.3	6.55±0.20	42.0+0.5/-0.4	6.0±0.25		0.63	70.36	112.10	7886	3351	3351	3351	3491	3072	4608	4.50	4.11	3.71	3.53	4.11	4.11	39.10
EE50-1	EE5013.6	1	49.6±0.50	6.80±0.15	18.0±0.20	4.0±0.15	43.2±0.5	6.3±0.20		0.60	62.10	103.70	6444	3570	3570	3570	3570	3454	4602	3.82	3.49	3.15	3.00	3.49	3.49	33.20
EE53-1	EE532116	1	53.0±0.50	8.10±0.15	21.00±0.25	4.40±0.15	45.4±0.45	7.60±0.15		0.43	67.20	157.00	10550	4910	4910	4910	5114	4501	6751	6.13	5.60	5.06	4.81	5.60	5.60	53.30
EE55-1	EE55/55/21	1	55.15±1.05	27.5±0.3	20.6±0.4	18.8±0.3	38.25±0.75	16.95±0.25		0.35	123.80	351.86	43560	6032	6032	6032	6283	5529	8294	25.30	23.10	20.90	19.86	23.10	23.10	220.00
EE56	EE5655	1	56.5±1.0	27.5±0.3	20.7±0.3	18.8±0.3	40min	17.2 ± 0/-0.5		0.38	131.70	345.95	45562	6512	6512	6512	6512	6267	8799	25.65	23.42	21.19	20.13	23.42	23.42	223.00
EE56-2	EE5612	1	56.0±0.50	6.20±0.1	25.0±0.20	3.80±0.15	51.4±0.5	5.0±0.1		0.59	71.15	119.83	8526	3578	3578	3578	3727	3280	4920	4.76	4.35	3.93	3.74	4.35	4.35	41.40