



NO.		尺寸(Unit: mm)							磁心参数				Al-value (nH/N ²)±25%						重量 (g/set)						
		A	B	C	D	E	F	F1	C1	Le	Ae	Ve	功耗Max (W/set)			功耗Max (W/set)									
		(mm ⁻¹)	(mm)	(mm ²)	(mm ³)	KP4	KP44	KP44A	KP47	KP90	KP95	KP4	KP44	KP44A	KP47	KP90	KP95								
EFS25-1	EFS2526A	25.50±0.30	13.25+0.0/-0.4	12.85±0.15	8.65±0.15	19.70±0.30	9.10±0.20	9.55±0.15	0.78	61.60	79.00	4866	2707	2707	2707	2820	2482	3723	2.76	2.52	2.28	2.17	2.52	2.52	24.00
EFS25-2	EFS2526B	25.05±0.65	12.90±0.2	12.45±0.25	9.85±0.25	19.20±0.4	8.80±0.25	8.30±0.3	0.81	60.20	74.00	4455	2606	2606	2606	2715	2389	3584	2.51	2.29	2.07	1.97	2.29	2.29	21.80
EFS25-3	EF2526	25.0±0.4	13.0±0.15	13.1±0.3	9.9±0.15	18.8±0.4	9.0±0.2	9.0±0.2	0.76	61.84	81.10	5018	2778	2778	2778	2894	2546	3820	2.92	2.67	2.41	2.29	2.67	2.67	25.40
EFS28-2	EFS2826	28.00±0.40	13.80±0.20	13.00±0.20	9.30±0.20	20.3+0/-0.45	9.00±0.20	8.60±0.20	0.67	62.39	93.15	5812	3151	3151	3151	3282	2888	4333	3.53	3.22	2.92	2.77	3.22	3.22	30.70