



NO.	Type	尺寸(Unit: mm)							磁心参数				Al-value (nH/N <sup>2</sup> )±25%					功耗Max (W/set)					重量 (g/set)
		A	B	C	D	E	F	F1	C1	Le	Ae	Ve	KP4	KP44	KP44A	KP90	KP95	KP4	KP44	KP44A	KP90	KP95	
		(mm <sup>-1</sup> )	(mm)	(mm <sup>2</sup> )	(mm <sup>3</sup> )																		
EPO9.5-1	1	9.50±0.30	4.55±0.25	10.05±0.35	3.15±0.15	7.40min	3.10±0.10	6.60±0.10	0.63	18.76	29.56	555	3326	3326	3326	3049	4574	0.33	0.30	0.28	0.30	0.30	2.90
EPO13-1	3	13.00±0.3	7.20±0.2	12.00±0.3	5.20±0.2	4.00±0.2	6.50±0.2		1.46	35.87	24.60	882	1446	1446	1446	1325	1988	0.54	0.49	0.45	0.49	0.49	4.70
EPO14-1	2	14.50±0.3	9.91±0.2	13.40±0.3	7.51±0.2	12.7(REF)	7.50±0.2	5.00±0.2	1.38	49.00	35.50	1740	1530	1530	1530	1402	2104	1.00	0.91	0.82	0.91	0.91	8.66
EPO14-2	4	14.3±0.3	6.1±0.15	10.9±0.20	3.7±0.15	11.0±0.3	4.4+0.1/-0.15	5.90+0.1/-0.15	0.64	20.70	32.30	669	2374	2374	2374	2318	2824	0.79	0.72	0.65	0.72	0.72	6.83