



NO.		Type	尺寸(Unit : mm)									磁心参数				AI-value (nH/N ²)±25%					功耗Max (W/set)					重量 (g/set)
			A	B	C	C1	D	E	E1	F	F1	C1 (mm ⁻¹)	Le (mm)	Ae (mm ²)	Ve (mm ³)	KP4	KP44	KP44A	KP90	KP95	KP4	KP44	KP44A	KP90	KP95	
EQR16-1	EQR1615	1	15.00±0.3	3.50±0.15	16.50±0.40		2.00±0.15		11.2±0.3	5.40±0.2	9.75±0.2	0.46	20.90	45.60	953	4589	4589	4589	4207	6311	0.61	0.56	0.50	0.56	0.56	5.30
EQR23-1	EQR2316.6	2	23.70±0.40	8.30±0.15	17.80±0.35	11.60±0.4	5.30±0.15	21.00±0.4	13.40min	12.20±0.25	9.60±0.25	0.50	45.90	92.40	4241	4307	4307	4307	4167	5553	2.28	2.08	1.88	2.08	2.08	19.80
EQR23-2	EQR2316.6	3	23.70±0.40	8.30±0.15	17.80±0.30	11.80ref	5.30±0.15	21.00±0.40	13.40min	12.20±0.25	9.60±0.25	0.45	43.90	97.00	4258	4673	4673	4673	4522	6004	2.30	2.10	1.90	2.10	2.10	20.00
EQR25-1	EQR2512	1	25.00±0.4	6.00±0.2	21.00±0.35		3.15±0.2	22±0.4	15.2±0.4	14.00±0.4	11.00±0.2	0.28	35.40	124.00	4390	7540	7540	7540	6912	10367	2.51	2.29	2.07	2.29	2.29	21.80
EQR31-1	EQR31/14.8/27.7	1	31.00±0.50	7.40±0.15	27.70±0.35		2.40±0.15	25.20±0.40	19.80±0.40	12.80±0.20	20.30±0.30	0.16	40.30	252.00	10160	11103	11103	11103	10801	13643	5.83	5.32	4.82	5.32	5.32	50.70