



Type.1

NO.	Type	尺寸(Unit : mm)									磁心参数				Al-value (nH/N ²)±25 %				功耗Max (W/set)				重量 (g/set)
		A	B	C	C1	D	E	E1	F	F1	C1	Le	Ae	Ve	KP4	KP44	KP47	KP95	KP4	KP44	KP47	KP95	
		(mm ⁻¹)	(mm)	(mm ²)	(mm ³)																		
LM5(RP8)	1	14.3±0.3	5.2±0.15	13.0±0.3	12.5±0.3	3.6±0.15	11.7±0.3	7.5min	5.4±0.15	8.1±0.2	0.75	34.80	26.40	920	2815	2815	2932	3870	0.54	0.49	0.42	0.49	4.70
LM6-1	1	17.60±0.45	5.70±0.15	14.18±0.3	13.28±0.3	4.00±0.1	13.40±0.3		10.00±0.3	7.00±0.2	0.52	27.10	52.10	1413	4060	4060	4229	5582	0.87	0.80	0.69	0.80	7.60
LM8-1	1	23.00±0.45	7.90±0.15	18.73±0.3	17.71±0.2	5.20±0.15	18.00±0.4		12.80±0.2	9.00±0.2	0.41	36.50	89.50	3267	5149	5149	5364	7080	2.06	1.88	1.62	1.88	17.90
LM8-2	1	23.00±0.45	8.0±0.15	17.71±0.2	17.25±0.2	5.30±0.15	18.00±0.4	14.10±0.3	12.80±0.2	9.00±0.2	0.42	37.20	88.80	3306	5027	5027	5236	6912	2.05	1.87	1.61	1.87	17.80
LM10-1	1	29.00±0.65	8.80±0.20	25.49±0.30	24.88±0.30	5.50±0.20	23.10±0.45		11.70±0.25	16.70±0.25	0.26	40.62	155.00	6308	8120	8120	8458	11165	3.93	3.59	3.09	3.59	34.20