



NO.	Type	尺寸(Unit: mm)													磁心参数				Al-value (nH/N ²)±25%					功耗Max (W/set)					重量 (g/set)	
		A	B	C	C1	C2	C3	C4	C5	D	E	E1	F	F1	C1	Le	Ae	Ve	KP4	KP44	KP44A	KP90	KP95	KP4	KP44	KP44A	KP90	KP95		
		(mm ⁻¹)	(mm)	(mm ²)	(mm ³)														(mm ⁻¹)	(mm)	(mm ²)	(mm ³)								
PT20-1	5	20.20±0.20	6.95±0.15	21.0±0.20	16.90±0.20	20.20±0.20	15.00±0.20	10.80±0.20		4.95±0.15	18.1±0.2	15.65±0.2	9.30±0.15		0.53	40.60	76.50	3106	3983	3983	3983	3651	5477	1.59	1.45	1.31	1.45	1.45	13.80	
PT26-1	5	25.80±0.30	9.40±0.15	26.4±0.30	22.00±0.30	25.80±0.30	20.80±0.30	13.00±0.30		6.80±0.15	23.6±0.3	19.6±0.3	12.00±0.15		0.37	45.00	122.00	5481	5706	5706	5706	5230	7845	3.28	2.99	2.71	2.99	2.99	28.50	
PT27-1	1	27.20±0.35	7.80±0.1	27.60±0.35	23.20±0.35	26.80±0.35	22.10±0.35	14.00±0.2	20.00±0.3	4.70±0.15	24.85±0.35	20.80±0.3	3.00(ref)	13.00±0.2	0.32	41.50	129.00	5353	6597	6597	6597	6048	9071	3.05	2.78	2.52	2.78	2.78	26.50	
PT27-2	2	27.20±0.35	9.40±0.1	27.60±0.35	23.20±0.35	22.10±0.35	22.10±0.35	14.00±0.2	26.80±0.35	6.80±0.15	24.85±0.35	20.80±0.3	13.00±0.2		0.39	49.70	129.00	6411	5413	5413	5413	4962	7443	3.67	3.35	3.03	3.35	3.35	31.90	
EEW25	3	24.50±0.4	5.90±0.2	13.00±0.3						3.40±0.2	18.20min		7.00±0.25		0.50	34.00	67.80	2305	4222	4222	4222	3870	5806	1.41	1.29	1.17	1.29	1.29	12.30	
PT30-1	2	30.4±0.2	9.40±0.2	13.60±0.1		26.80±0.2	22.20±0.2	14.00±0.2	19.8±0.2	6.80±0.2	26.80±0.2	18.10±0.2			0.32	41.50	129.00	5353	6597	6597	6597	6048	9071	4.17	3.81	3.45	3.81	3.81	36.30	